


## **TIS Mars Panel**

### **12/8/4 Buttons**

Model: MRS-12G MRS-8G MRS-4G

Data Sheet Rev 1.1



### **Safety instructions**

Electrical equipment may only be installed and fitted by electrically skilled persons. Failure to observe the instructions may cause damage to the device and other hazards. These instructions are an integral part of the product, and must remain with the end customer.

### **Basic information**

This device is a product of the TIS system. It is a wall mount Panel with 12/8/4 buttons that can be Programmed to control lights, scenes, curtain, TV, and all other devices on the same TIS network, technical knowledge obtained in TIS training courses is a prerequisite to proper understanding how to install device. Advanced Programming knowledge about software obtained in the advanced training courses.

### **Intended use**

To control home appliance, lights on/off, scene and curtain in each room or area.

## Product Characteristics

<b>Inputs</b>	IR receiver Using Panel Addition	TIS Infrared code receiver 2-3 Digital Inputs
<b>Outputs</b>	Using Panel Addition 3R Using Panel Addition 3DL-12V Using Panel Addition 2DL-IRE	3 Relay Output 3A/5A 12V DC 50mA Output IR Emitter
<b>TIS Bus</b>	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <35 mA / 24 V DC
<b>Protection</b>	Protection	Reverse Polarity Protection ESD Protection
<b>Reaction time</b>		approx. 20ms
<b>Mounting</b>	Wall mount	by 2 screws on the back box (UK, Europe, US)
<b>Connection terminal</b>	Data	2 mail pins connectors to fit in panel addition
<b>Operating and display elements</b>	12/8/4 Buttons Indicator LED Backlight TIS bus Upgrading	For controlling lights, scene, etc... 12/8/4 Blue and Orange LED 6/4/2 pairs of White neon LED TIS Protocol massages and commands 1 X mini USB for up to date upgrading.
<b>Functions</b>	1 Press Long Press Double click IR receiver	ON/OFF/Scene Dim or ramp the lights Extra Scene Music, scene, lights control
<b>Weight</b>	Without packaging	140 g
<b>Dimensions</b>	Width x length x height	90 * 125 * 15-21 peak
<b>Housing</b>	Materials Casing color  Internal Parts color	PC anti fire Black/Titanium, Silver, White, Champaign, coal, Bronze or special color Black & White
<b>Temperature range</b>	Operation Storage Transport	-10...60°C -20...50°C -25...75°C
<b>Air humidity</b>		<85% non-condensing

For installation steps and wiring diagram please read “Mars Panel installation steps” and “Mars wiring diagram” documents.

### Warranty

We provide a warranty as provided for by law.

Product serial number is provided by each device.

Please send the description of the defect with Product S/N to our dealer network.

[info@tissmarthome.com](mailto:info@tissmarthome.com)

[www.tissmarthome.com](http://www.tissmarthome.com)